

Aluminum Square Anchor Base Poles

Height	Thickness	Dimension	Weight	Maximum EPA				Catalog #	Anchor Bolts
				130	140	150	160		
8	0.125	4	300	12.50	10.60	9.00	7.80	ASAB-4-0.125-8	A
10	0.125	4	251	9.30	7.80	6.50	9.00	ASAB-4-0.125-10	A
10	0.188	4	300	14.60	12.40	10.50	9.00	ASAB-4-0.188-10	A
12	0.125	4	174	7.20	5.80	4.80	3.90	ASAB-4-0.125-12	B
12	0.188	4	249	11.40	9.50	8.00	6.70	ASAB-4-0.188-12	B
12	0.188	5	300	22.20	18.70	15.90	13.60	ASAB-5-0.188-12	B
14	0.125	4	127	5.40	4.30	3.40	2.60	ASAB-4-0.125-14	B
14	0.188	4	182	9.10	7.40	6.10	5.00	ASAB-4-0.188-14	B
14	0.188	5	300	17.70	14.70	12.30	10.30	ASAB-5-0.188-14	B
15	0.125	4	111	4.60	3.60	2.70	2.00	ASAB-4-0.125-15	B
15	0.188	4	158	8.10	6.50	5.30	4.30	ASAB-4-0.188-15	B
15	0.188	5	300	15.70	13.00	10.80	9.00	ASAB-5-0.188-15	B
16	0.125	4	97	3.90	2.90	2.10	1.50	ASAB-4-0.125-16	B
16	0.188	4	139	7.10	5.70	4.50	3.60	ASAB-4-0.188-16	B
16	0.188	5	284	14.00	11.40	9.40	7.70	ASAB-5-0.188-16	B
18	0.125	4	76	2.60	1.70	1.00	-	ASAB-4-0.125-18	B
18	0.188	4	110	5.30	4.10	3.10	2.30	ASAB-4-0.188-18	B
18	0.250	4	139	7.80	6.30	5.00	3.90	ASAB-4-0.25-18	B
18	0.188	5	224	11.00	8.80	7.00	5.60	ASAB-5-0.188-18	B
20	0.125	4	62	1.40	0.70	-	-	ASAB-4-0.125-20	B
20	0.188	4	89	3.80	2.80	1.90	1.20	ASAB-4-0.188-20	B
20	0.250	4	112	6.00	4.70	3.50	2.60	ASAB-4-0.25-20	B
20	0.188	5	181	8.60	6.60	5.00	3.70	ASAB-5-0.188-20	B
20	0.250	5	232	12.70	10.20	8.10	6.50	ASAB-5-0.25-20	B
20	0.188	6	300	11.50	8.90	6.80	5.10	ASAB-6-0.188-20	B
20	0.250	6	300	17.40	14.00	11.30	9.00	ASAB-6-0.25-20	B
25	0.188	5	115	3.70	2.20	1.00	-	ASAB-5-0.188-25	B
25	0.250	5	147	6.80	4.90	3.40	2.10	ASAB-5-0.25-25	B
25	0.188	6	203	5.20	3.20	1.70	-	ASAB-6-0.188-25	B
25	0.250	6	262	9.40	6.90	4.80	3.20	ASAB-6-0.25-25	B
25	0.250	6.625	300	14.00	10.60	7.90	5.70	ASAB-7-0.25-25	B

Colors	W	White	Bolts	A	5/8"
	B	Black		B	3/4"
	C	Cocoa, Bronze		C	1"

These poles quoted on an as-required basis due to fluctuation in aluminum market prices

Steel Square Anchor Base Poles

Height	Thickness	Dimension	Weight	Maximum EPA				Catalog #	Anchor Bolts
				130	140	150	160		
10	11	4	300	17.90	15.00	12.80	10.90	SSAB-4-11.-10	A
12	11	4	300	14.10	11.70	9.80	8.20	SSAB-4-11.-12	B
14	11	4	300	11.10	9.00	7.40	6.00	SSAB-4-11.-14	B
15	11	4	295	9.80	7.90	6.40	5.10	SSAB-4-11.-15	B
15	7	4	300	16.40	13.70	11.50	9.70	SSAB-4-07.-15	B
16	11	4	259	8.80	7.00	5.50	4.30	SSAB-4-11.-16	B
16	7	4	300	14.80	12.30	10.20	8.50	SSAB-4-07.-16	B
18	11	4	204	6.80	5.20	3.90	2.90	SSAB-4-11.-18	B
18	7	4	284	12.00	9.80	8.00	6.50	SSAB-4-07.-18	B
20	11	4	165	5.10	3.70	2.50	1.60	SSAB-4-11.-20	B
20	11	5	300	7.90	5.80	4.20	2.80	SSAB-5-11.-20	B
20	7	4	229	9.90	7.90	6.30	5.00	SSAB-4-07.-20	B
20	7	5	300	18.10	14.80	12.10	9.90	SSAB-5-07.-20	B
22	11	4	136	3.60	2.30	1.20	-	SSAB-4-11.-22	B
22	11	5	275	5.70	3.80	2.30	1.10	SSAB-5-11.-22	B
22	7	4	189	8.00	6.20	4.80	3.60	SSAB-4-07.-22	B
22	7	5	300	14.90	11.90	9.50	7.50	SSAB-5-07.-22	B
25	11	5	212	2.90	1.30	-	-	SSAB-5-11.-25	B
25	7	4	146	5.60	4.10	2.80	1.80	SSAB-4-07.-25	B
25	7	5	300	10.80	8.30	6.20	4.60	SSAB-5-07.-25	B

Colors	W	White	Bolts	A	5/8"
	B	Black		B	3/4"
	C	Cocoa, Bronze		C	1"

These poles quoted on an as-required basis due to fluctuation in market prices